

## ANSI D-RING COBRA® PRO STYLE

**38 mm**

Art.no.: FX38KVD



This innovative component is a synergistic hybrid of two standard components of safety industry hardware: the stainless-steel d-ring and the ANSI COBRA® PRO STYLE - a buckle which meets the highest safety requirements for its users. Its unique construction prevents the D-Ring from getting squeezed against the webbing and therefore guarantees easy handling.


The ANSI COBRA® PRO STYLE, certified according to the American safety standard ANSI, is thicker and even stronger than the COBRA® PRO STYLE. This buckle is marked according to the ANSI norm with a guaranteed tensile strength of 15 kN. However, we guarantee 18 kN for the buckle and 22 kN for the d-ring and point this out in the technical specifications accordingly. Certified according to ANSI/ASSE and upon request NFPA.

### use cases:

PPE, Fashion, air sports, tactical, equipment

## Technical specifications

<b>BODY</b>	<b>Material:</b> aluminium <b>Color:</b> black <b>Finish:</b> ktl coated
<b>CLIPS</b>	<b>Material:</b> brass <b>Color:</b> colorless <b>Finish:</b> polished
<b>BAR</b>	<b>Material:</b> stainless steel <b>Color:</b> colorless <b>Finish:</b> polished
<b>D-RING</b>	<b>Material:</b> stainless steel <b>Color:</b> colorless <b>Finish:</b> polished
<b>BREAKING LOAD TENSILE STRENGTH</b>	18 kN
<b>BREAKING LOAD D-RING</b>	22 kN

<b>WEIGHT</b>	139 g
<b>RECOMM. WEBBING WIDTH MALE PART</b>	38 mm
<b>RECOMM. WEBBING WIDTH FEMALE PART</b>	38 mm
<b>OUTER DIMENSION LENGTH</b>	69 mm
<b>OUTER DIMENSION WIDTH</b>	58 mm
<b>OUTER DIMENSION DEPTH</b>	14 mm
<b>TECHNICAL DESIGN MALE PART</b>	adjustable
<b>TECHNICAL DESIGN FEMALE PART</b>	non adjustable with integrated D-ring
<b>SINGLE PIECE TESTED</b>	Yes
<b>COUNTRY OF ORIGIN</b>	Austria
 <b>Patented</b>	
<b>STANDARDS</b>	ANSI/ASSE Z359.12-2019, CSA Z259.12-2016 Class I, EN358:2018-11 (partial)



